

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Nowo Metal Roof Top WB

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Roof paint

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

NOWOCOAT INDUSTRIAL A/S

Staalvej 3

6000 Kolding

tlf: +45 7550 1111

mail@nowocoat.dk

Contact person

Annette Søgaard

E-mail

mail@nowocoat.dk

SDS date

2018-03-22

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aquatic Chronic 3; H412

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)

Not applicable

Signal word

-

Hazard statement(s)

Harmful to aquatic life with long lasting effects. (H412)

Safety statement(s)

General If medical advice is needed, have product container or label at hand. (P101).

Prevention Avoid release to the environment. (P273).

Response -

Storage -

Disposal Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

Not applicable

2.3. Other hazards

Not applicable.

Additional labelling

Contains 5-Chloro-2-methyl-4-isothiazolin-3-one. May produce an allergic reaction. (EUH208).

Additional warnings

Not applicable.

VOC

Not applicable.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

| | |
|----------------------|---|
| NAME: | Limestone |
| IDENTIFICATION NOS.: | CAS-no: 1317-65-3 EC-no: 215-279-6 |
| CONTENT: | 2.5 - <5% |
| CLP CLASSIFICATION: | NA |
| NAME: | Talc (Mg ₃ H ₂ (SiO ₃) ₄) |
| IDENTIFICATION NOS.: | CAS-no: 14807-96-6 EC-no: 238-877-9 |
| CONTENT: | 2.5 - <5% |
| CLP CLASSIFICATION: | NA |
| NAME: | Trizinc bis(orthophosphate) |
| IDENTIFICATION NOS.: | CAS-no: 7779-90-0 EC-no: 231-944-3 Index-no: 030-011-00-6 |
| CONTENT: | 0.25 - <1% |
| CLP CLASSIFICATION: | Aquatic Acute 1, Aquatic Chronic 1 H400, H410 |
| NAME: | Ammonia, aqueous solution |
| IDENTIFICATION NOS.: | CAS-no: 1336-21-6 EC-no: 215-647-6 Index-no: 007-001-01-2 |
| CONTENT: | 0.1 - <0.25% |
| CLP CLASSIFICATION: | Skin Corr. 1B, Aquatic Acute 1 H314, H400 |
| NAME: | Zinc oxide |
| IDENTIFICATION NOS.: | CAS-no: 1314-13-2 EC-no: 215-222-5 Index-no: 030-013-00-7 |
| CONTENT: | 0.1 - <0.25% |
| CLP CLASSIFICATION: | Aquatic Acute 1, Aquatic Chronic 1 H400, H410 |
| NAME: | 5-Chloro-2-methyl-4-isothiazolin-3-one |
| IDENTIFICATION NOS.: | CAS-no: 55965-84-9 Index-no: 613-167-00-5 |
| CONTENT: | <0.0015% |
| CLP CLASSIFICATION: | Acute tox. 3, Skin Corr. 1B, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1 H301, H311, H314, H317, H331, H400, H410 |

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

ATEmix(inhale, vapour) > 20
ATEmix(dermal) > 2000
ATEmix(oral) > 2000
 $N_{\text{chronic}} (\text{CAT } 3) \text{ Sum} = \text{Sum}(\text{Ci}/(\text{M}(\text{chronic})^i * 25) * 0.1 * 10^{\wedge} \text{CAT}_i) = 2,6624 - 3,9936$
 $N_{\text{acute}} (\text{CAT } 1) \text{ Sum} = \text{Sum}(\text{Ci}/\text{M}(\text{acute})^i * 25) = 0,0458904 - 0,0688356$

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that may trigger an allergic reaction to predisposed persons.

4.3. Indication of any immediate medical attention and special treatment needed

Nothing special.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Some metal oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

No specific requirements.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. It is recommended to install waste collection trays to prevent emissions to the waste water system and surrounding environment. See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

Talc ($Mg_3H_2(SiO_3)_4$)

Long-term exposure limit (8-hour TWA reference period): - ppm | 1 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Limestone

Long-term exposure limit (8-hour TWA reference period): - ppm | - mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

DNEL / PNEC

DNEL (Trizinc bis(orthophosphate)): 5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Trizinc bis(orthophosphate)): 83 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Trizinc bis(orthophosphate)): 2.5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Trizinc bis(orthophosphate)): 83 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Trizinc bis(orthophosphate)): 830 µg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Zinc oxide): 5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Zinc oxide): 500 µg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (Zinc oxide): 83 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (Zinc oxide): 2.5 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Zinc oxide): 83 mg/kg bw/day

Exposure: Dermal

Duration of Exposure: Long term – Systemic effects - General population

DNEL (Zinc oxide): 830 µg/kg bw/day

Exposure: Oral

Duration of Exposure: Long term – Systemic effects - General population

PNEC (Trizinc bis(orthophosphate)): 20.6 µg/L

Exposure: Freshwater

Duration of Exposure: Single

PNEC (Trizinc bis(orthophosphate)): 6.1 µg/L

Exposure: Marine water

Duration of Exposure: Single

PNEC (Trizinc bis(orthophosphate)): 35.6 mg/kg soil dw

Exposure: Soil

Duration of Exposure: Single

PNEC (Zinc oxide): 20.6 µg/L

Exposure: Freshwater

Duration of Exposure: Single

PNEC (Zinc oxide): 6.1 µg/L

Exposure: Marine water

Duration of Exposure: Single

PNEC (Zinc oxide): 35.6 mg/kg soil dw

Exposure: Soil

Duration of Exposure: Single

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements.

Skin protection

No specific requirements.

Hand protection

Recommended: Nitrile rubber. See the manufacturer's instructions.

Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------|
| Form | Liquid |
| Colour | Black |
| Odour | No data available. |
| Odour threshold (ppm) | No data available. |
| pH | No data available. |
| Viscosity (40°C) | No data available. |
| Density (g/cm ³) | 1,1-1,3 |
| Phase changes | |
| Melting point (°C) | No data available. |
| Boiling point (°C) | No data available. |
| Vapour pressure | No data available. |
| Decomposition temperature (°C) | No data available. |
| Evaporation rate (n-butylacetate = 100) | No data available. |
| Data on fire and explosion hazards | |
| Flash point (°C) | No data available. |
| Ignition (°C) | No data available. |
| Auto flammability (°C) | No data available. |
| Explosion limits (% v/v) | No data available. |
| Explosive properties | No data available. |
| Solubility | |
| Solubility in water | Soluble |
| n-octanol/water coefficient | No data available. |

9.2. Other information

Solubility in fat (g/L)

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: Zinc oxide

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 2000 - 5000 mg/kg bw

Substance: Zinc oxide

Species: Rat

Test: LD50

Route of exposure: Dermal

Result: 2000 mg/kg bw

Substance: Zinc oxide

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 1.79 - 5.7 mg/L air (4 h)

Substance: Trizinc bis(orthophosphate)

Species: Rat

Test: LD50

Route of exposure: Oral

Result: 5000 mg/kg bw

Skin corrosion/irritation

No data available.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

This product contains substances that may trigger an allergic reaction to predisposed persons.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Nothing special.

SECTION 12: Ecological information

12.1. Toxicity

Substance: Zinc oxide
 Species: Daphnia
 Test: EC50
 Duration: 48 h
 Result: 155 µg/L

Substance: Zinc oxide
 Species: Fish
 Test: LC50
 Duration: 96 h
 Result: 112 - 8062 µg/L

Substance: Trizinc bis(orthophosphate)
 Species: Daphnia
 Test: EC50
 Duration: 48 h
 Result: 155 - 2909 µg/L

Substance: Trizinc bis(orthophosphate)
 Species: Fish
 Test: LC50
 Duration: 96 h
 Result: 112 - 2920 µg/L

12.2. Persistence and degradability

| Substance | Biodegradability | Test | Result |
|--------------------|------------------|------|--------|
| No data available. | | | |

12.3. Bioaccumulative potential

| Substance | Potential bioaccumulation | LogPow | BCF |
|--------------------|---------------------------|--------|-----|
| No data available. | | | |

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which due to poor biodegradability, may cause adverse long-term effects to the aquatic environment,

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

| | |
|-----------|---|
| EWC code | |
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |

Specific labelling

-

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

| | |
|----------------------------------|---|
| 14.1. UN number | - |
| 14.2. UN proper shipping name | - |
| 14.3. Transport hazard class(es) | - |
| 14.4. Packing group | - |
| Notes | - |
| Tunnel restriction code | - |

IMDG

| | |
|-----------------------|---|
| UN-no. | - |
| Proper Shipping Name | - |
| Class | - |
| PG* | - |
| EmS | - |
| MP** | - |
| Hazardous constituent | - |

IATA/ICAO

| | |
|----------------------|---|
| UN-no. | - |
| Proper Shipping Name | - |
| Class | - |
| PG* | - |

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

-

Demands for specific education

-

Additional information

Not applicable

Seveso

-

Sources

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No.

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H301 - Toxic if swallowed.

H311 - Toxic in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H331 - Toxic if inhaled.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable.

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

Annette

**Date of last essential change
(First cipher in SDS version)**

-

**Date of last minor change
(Last cipher in SDS version)**

-